

Surface finishing techniques to increase the life of subsea components

www.cwst.com | www.cwst.co.uk

Subsea is one of the most hostile environments in which to operate critical equipment with pressures increasing by 10bar for every 100m of depth and plans for ultra-deep oil sites only serve to increase the challenges.

Materials chosen for subsea applications such as mandrels, drill collars, rock bits, ball valves and valve bodies are often chosen for their surface properties and characteristics which can mean using expensive alloys with long lead times and difficult machining attributes. It is however possible to engineer the desired surface requirements using surface modification and finishing technologies. These can be tailored and/or combined to meet the exact demands of your operating environment, reducing manufacturing and maintenance costs and extending component life.

Environmental resistance and protection

For example, Thermal Spray coatings can be used to deposit a film of pure metal, alloy or ceramic oxide onto the surface, making components resistant to wear, corrosion, erosion and chemical attack, as well as increasing thermal insulation and electrical conductivity/insulation.

Thermal spray can be applied using a range of processes including high-velocity oxy fuel, plasma, arc wire, flame spray and cold

spray. The choice of application process is assessed according to the operating parameters required.

The operation principle is the same for all and involves heating particles, usually to a molten or semi-molten condition and propelling them at high speed onto the component surface, which has been pre-roughened. When the particle hits the roughened surface it flattens and shrinks as it cools, gripping the surface and creating a strong mechanical bond. The coating is then built up in layers to the desired thickness.

Extending fatigue life

Inducing a layer of compressive residual stress into the component surface can significantly increase fatigue life, preventing fatigue cracks which propagate as a result of cyclic stresses that are often far lower than the static design stress considered for the component.

The damage is cumulative and permanent, with failure occurring when cracks propagate to an extent where the remaining



section is unable to withstand the application of a single load.

Harmful tensile residual stresses, often introduced during manufacturing, are effectively added to the operating stresses, accelerating fatigue damage. These stresses can be completely reversed with surface compression techniques.

The most cost-effective and well-proven method of inducing a protective compressive layer is to carry out a controlled shot peening operation. This involves firing spherical media at the component surface at a controlled angle and velocity causing elastic plastic deformation with each indentation. As the substrate material tries to rebound the conflict creates an effective long lasting compressive layer which can be driven deep enough below the surface to sit below pre-existing and post-manufacturing initiation sites such as pits, scratches and notches.

Shot peening can also be combined with thermal spray coatings to provide a protective layer beneath the coating interface, improving both surface characteristics and fatigue resistance.

In addition to improving the performance of new components, thermal spray and shot peening technologies are commonly used in the repair and overhaul of worn and damaged components.

Neil Sheward, Technical Services Manager, Curtiss-Wright Surface Technologies, Derby Tel: 01332 756076



Why should you choose Curtiss-Wright Surface Technologies (CWST) to deliver your surface treatments:

A worldwide supported network service of over 75 facilities, including on site field crews

We offer a diverse range of quality surface treatments including:

- Controlled shot peening
- Shot peen forming
- Laser peening
- Engineered coatings
- C.A.S.E.™ super finishing
- Surface texturing
- Material testing
- Repair and overhaul

Proud history of experience and innovation dating back to the Wright Brothers and Glen Curtiss who formed the Curtiss-Wright Corporation in 1929

As a single source for all your surface treatments we can improve your turnaround times and save you money

Customer's trust us to improve the performance, strength and life of their components, including the repair and overhaul of worn components

Long experience in protecting components from fatigue, corrosion, wear, galling, fretting and environmental attack in key industries

We maintain all appropriate customer and industry quality approvals including ISO 9001:2008, NADCAP, AS9100 Rev C and ISO 13485

Tailoring our services to meet your needs



The Dublin Spire – a stunning example of our surface texturing technique showing the versatility of controlled shot peening

EUROPEAN CORPORATE OFFICE

Metal Improvement Company Curtiss-Wright

Hambridge Lane, Newbury
Berkshire RG14 5TU, UK

- T: +44 (0)1635 279621
- E: eurosales@cwst.com
- W: www.cwst.co.uk

USA COMPANY HQ

Metal Improvement Company Curtiss-Wright

80 Route 4 East, Suite 310
Paramus, New Jersey 07652, USA

- T: +1 (201) 843 7800
- E: info@cwst.com
- W: www.cwst.com

PARENT COMPANY HQ

Curtiss-Wright Corporation

13925 Ballantyne Corporate Place
Suite 400, Charlotte, NC 28277

- T: +1 (973) 541 3700
- F: +1 (973) 541 3699
- W: www.curtisswright.com

